



LEVEL BEST[®] BOX BLADES

PD72 | PD84 | PD96



SPECIFICATIONS

- These box blades are 2D or 3D Topcon grade-control ready.
- Push-pull design moves the material for fine grading.
- Two cylinders provide cross-slope operation.
- All cutting edges are reversible.
- Convex mirror allows material visibility.
- Foam-filled tires pivot on an oscillating axle.
- These Level Best box blades are optimized to work with John Deere skid steer loaders (SSLs) and compact track loaders (CTLs). They're also compatible with most competitive models.

	PD72	PD84	PD96
Weight	915 kg (2,020 lb.)	940 kg (2,070 lb.)	980 kg (2,155 lb.)
Width			
Box	1830 mm (72 in.)	2130 mm (84 in.)	2440 mm (96 in.)
Overall	1910 mm (75.25 in.)	2220 mm (87.25 in.)	2520 mm (99.25 in.)
Total Length	1810 mm (71.25 in.)	1810 mm (71.25 in.)	1810 mm (71.25 in.)
Box Capacity			
Front	0.33 m ³ (11.5 cu. ft.)	0.38 m ³ (13.4 cu. ft.)	0.43 m ³ (15.3 cu. ft.)
Rear	0.20 m ³ (7.0 cu. ft.)	0.23 m ³ (8.0 cu. ft.)	0.25 m ³ (9.0 cu. ft.)
Hydraulic Flow	57–95 L/min. (15–25 gpm)	57–95 L/min. (15–25 gpm)	57–95 L/min. (15–25 gpm)
Maximum Operature Pressure	28 000 kPa (4,000 psi)	28 000 kPa (4,000 psi)	28 000 kPa (4,000 psi)
Vehicle Compatibility	316GR and 318G SSLs; 317G CTL	318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs	320G, 324G, 330G, and 332G SSLs; 325G, 331G, and 333G CTLs