

MATERIAL/MANURE SCRAPERS

MS60 | MS72 | MS84 | MS96



SPECIFICATIONS

- Effortlessly push or scrape manure, mud, light snow, and other wet or sloppy materials. Rubber cutting edges are ideal for cleanup on hard surfaces such as concrete and asphalt.
- Standard pull-back edge works well for cleaning out corners and difficult-to-reach places.
- Bolt-on rubber edges are easy to change and reversible, for extended wear life.
- These scrapers are optimized to work with John Deere skid steer loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs). They're also compatible with most competitive models.

	MS60	MS72	MS84	MS96
Weight	208 kg (458 lb.)	234 kg (516 lb.)	267 kg (589 lb.)	298 kg (656 lb.)
Width	1524 mm (60 in.)	1829 mm (72 in.)	2134 mm (84 in.)	2438 mm (96 in.)
Height	762 mm (30 in.)	762 mm (30 in.)	762 mm (30 in.)	762 mm (30 in.)
Depth	762 mm (30 in.)	762 mm (30 in.)	762 mm (30 in.)	762 mm (30 in.)
Connection				
Hydraulic	None	None	None	None
Electrical	None	None	None	None
Vehicle Compatibility	316GR and 318G SSLs	316GR, 318G, 320G, and 324G SSLs; 317G CTL	320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs; 204L*, 244L*, 304L*, and 324L* CWLs	320G, 324G, 330G, and 332G SSLs; 325G, 331G, and 333G CTLs; 204L*, 244L*, 304L*, and 324L* CWLs

*Requires skid-steer-style Quik-Tatch™ coupler for operation.

