



# ROLLER LEVEL

RL84

## SPECIFICATIONS

- The John Deere roller level delivers reliable, cost-efficient productivity for finish-grade work.
- Front roller position offers unobstructed visibility and provides total control when contouring, grading, cutting, and smoothing flat or significantly sloped terrain.
- Front and rear cutting edges make quick work of tough site-prep and grading tasks. Use either or both edges to spread loose material and for quickly cutting or scraping hard-pack without disturbing the base below.
- Roller pulverizes clumps and clods for a smoother finish in loose soil.
- Designed for minimal maintenance and maximum uptime, with only two greaseable bearings, two replaceable cutting edges, and no hydraulics.
- This roller level is optimized to work with John Deere skid steer loaders (SSLs) and compact track loaders (CTLs). It's also compatible with many competitive models.





<b>RL84</b>	
<b>Weight</b>	734 kg (1,620 lb.)
<b>Width</b>	
Overall	2367 mm (93.3 in.)
Box	2133 mm (84 in.)
<b>Length</b>	1694 mm (66.7 in.)
<b>Height</b>	650 mm (25.6 in.)
<b>Cutting Edge, Bolt-On (2)</b>	Standard
Front	16 x 152 x 2134 mm (0.625 x 6 x 84 in.)
Rear	16 x 152 x 2134 mm (0.625 x 6 x 84 in.)
<b>Roller Diameter</b>	330 mm (13 in.)
<b>Hydraulics</b>	No
<b>Greaseable Bearings (2)</b>	Standard
<b>Vehicle Compatibility</b>	330G and 332G SSLs; 317G, 325G, 331G, and 333G CTLs