



ROOT RAKES

RR72 | RR78 | RR84



SPECIFICATIONS

- Designed specifically for land clearing, ground leveling, and moving materials away from buildings and obstructions more quickly and economically than dozer blades.
- Alloy-steel construction, replaceable pin-on teeth, and zinc-plated greaseable pivot pins with protected zerks and hardened-steel bushings ruggedly resist impact.
- Weld-on “D” ring enables the tackling of a wide variety of jobsite tasks.
- Handily gather rocks and debris while allowing soil to sift through, for minimal site and landscape disturbance.
- Attachment height and width help shield the front of the machine against large piles of brush or jagged scrap.
- These root rakes are optimized to work with John Deere skid steer loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs). They’re also compatible with many competitive models.

	RR72	RR78	RR84
Overall Width	1830 mm (72 in.)	1980 mm (78 in.)	2135 mm (84 in.)
Overall Height	990 mm (38.9 in.)	990 mm (38.9 in.)	990 mm (38.9 in.)
Overall Length	780 mm (30.8 in.)	780 mm (30.8 in.)	780 mm (30.8 in.)
Grapple			
Width	1780 mm (70 in.)	1780 mm (70 in.)	1780 mm (70 in.)
Opening	1295 mm (51 in.)	1295 mm (51 in.)	1295 mm (51 in.)
Tooth Position	635 mm (25 in.)	635 mm (25 in.)	635 mm (25 in.)
Tine Spacing	240 mm (9.5 in.)	255 mm (10 in.)	215 mm (8.5 in.)
Weight	497 kg (1,095 lb.)	522 kg (1,150 lb.)	553 kg (1,220 lb.)
Cylinder			
Bore	65 mm (2.5 in.)	65 mm (2.5 in.)	65 mm (2.5 in.)
Stroke	230 mm (9 in.)	230 mm (9 in.)	230 mm (9 in.)
Rod Diameter	40 mm (1.5 in.)	40 mm (1.5 in.)	40 mm (1.5 in.)
Vehicle Compatibility	318G, 320G, 324G, and 330G SSLs; 317G and 325G CTLs; 204L* and 304L* CWLs	320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs; 204L*, 244L*, 304L*, and 324L* CWLs	330G and 332G SSLs; 325G, 331G, and 333G CTLs; 204L*, 244L*, 304L*, and 324L* CWLs

*Requires skid-steer-style Quik-Tatch™ coupler for operation.