

SNOW/UTILITY BLADES

BL6B / BL7B / BL8B / BL9B / BL10B



SPECIFICATIONS

- John Deere snow/utility blades provide additional productivity in snow removal and light dirt work.
- Blade angles hydraulically 30 degrees, right or left. Adjustable skid shoes are standard.
- Blade oscillates five degrees, right or left.
- Four trip springs help protect the vehicle from sudden impacts with obstacles when blading snow. Trip springs can be locked out for light grading and dirt work.
- Bolt-on replaceable six-inch edge is 0.5-inches thick. Available rubber cutting edges prevent damage to decorative surfaces.
- Blade height is 28 inches; an 8-inch full-length extension is available.
- These blades are optimized to work with John Deere skid steer loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs). They are also compatible with many competitive models.

	BL6B	BL7B	BL8B	BL9B	BL10B
Width	1829 mm (72 in.)	2134 mm (84 in.)	2438 mm (96 in.)	2743 mm (108 in.)	3048 mm (120 in.)
Angled Width	1575 mm (62 in.)	1829 mm (72 in.)	2108 mm (83 in.)	2362 mm (93 in.)	2591 mm (102 in.)
Height	711 mm (28 in.)	711 mm (28 in.)	711 mm (28 in.)	711 mm (28 in.)	711 mm (28 in.)
Weight	432 kg (954 lb.)	461 kg (1,016 lb.)	489 kg (1,078 lb.)	512 kg (1,128 lb.)	540 kg (1,190 lb.)
Vehicle Compatibility	316GR and 318G SSLs; 317G CTL	316GR, 318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs	318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs	320G, 324G, 330G, and 332G SSLs; 325G, 331G, and 333G CTLs; 204L*, 244L*, 304L*, and 324L* CWLs	330G and 332G SSLs; 325G, 331G, and 333G CTLs; 204L*, 244L*, 304L*, and 324L* CWLs

**Requires skid-steer-style Quik-Tatch™ coupler for operation.*



