



SNOW/UTILITY V-BLADES

BV6 / BV8 / BV9



SPECIFICATIONS

- John Deere snow/utility V-blades provide multifunction versatility for snow removal and light dirt work.
- Blades angle hydraulically to four positions: **straight** for larger cuts, **V-configuration** for pushing through hard pack, **scoop** (both sides inward) for easy snow stacking, and **30 degrees right or left**.
- Steel cutting edge is standard. Available rubber cutting edge helps prevent damage to decorative surfaces.
- Adjustable skid shoes for vertical blade productivity are standard.
- Trip springs help protect the vehicle from sudden impacts with concealed obstacles and can be locked out for light grading and dirt work.
- Electrohydraulic (EH) valve for independent blade function is adjustable from the cab.*
- Top blade extension for extra carrying capacity is available.
- These V-blades are optimized to work with John Deere skid steer loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs). They are also compatible with many competitive models. See your dealer for details on attachment-control kits if not ordered as a factory-installed option.

*SSLs, CTLs, and CWLs require 1/2-inch auxiliary couplers and a 14-pin electrical connector for blade operation.

	BV6	BV8	BV9
Width			
Straight	1880 mm (74 in.)	2489 mm (98 in.)	2794 mm (110 in.)
V-Configuration	1638 mm (64.5 in.)	2172 mm (85.5 in.)	2438 mm (96 in.)
Scoop	1600 mm (63 in.)	2134 mm (84 in.)	2413 mm (95 in.)
30-deg. Angle	1626 mm (64 in.)	2159 mm (85 in.)	2416 mm (95 in.)
Height	711 mm (28 in.)	711 mm (28 in.)	711 mm (28 in.)
Oscillation	±10 deg.	±10 deg.	±10 deg.
Operating Weight	441 kg (972 lb.)	480 kg (1,058 lb.)	500 kg (1,102 lb.)
Vehicle Compatibility	316GR and 318G SSLs	318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs; 204L*, 244L*, 304L*, and 324L* CWLs	318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs; 204L*, 244L*, 304L*, and 324L* CWLs

*Requires skid-steer-style Quik-Tatch™ coupler for operation.